AMENDMENTS TO THE CLAIMS:

The following is a complete listing of the claims.

- 1. (Currently amended) The A floor covering comprising as polymer binder at least one elastomer as a polymeric binder based on at least one polyolefin with a density < 0.910 g/cm³, and at least one grafted copolymer, wherein the grafted copolymer is maleic acid anhydride grafted HD polyethylene.
- 2. (Previously presented) The floor covering as claimed in Claim 1, wherein the polyolefin has a density of 0.85 0.892 g/cm³.
- (Currently amended) The floor covering as claimed in Claim 1, wherein the polyolefin is selected from among the class of VLD very low density (VLD) PE polymers.
- 4. (Currently amended) The floor covering as claimed in Claim 1, wherein the polyolefin is a mixture of at least two ethylene copolymers, wherein the ethylene copolymer mixture comprises a copolymer (a) as the main polymer with a density of 0.89 0.91 g/cm³ and a copolymer (b) to control rheology and elasticity with a density of 0.86–0.88 g/cm³ and an MFI a melt flow index (MFI) > 3.
- 5. (Previously presented) The floor covering as claimed in Claim 4, wherein the copolymers (a) and (b) are present at a weight ratio of 4:1 to 3:2.

- 6. (Previously presented) The floor covering as claimed in Claim 4, wherein the copolymers (a) and (b) are copolymers of ethylene and octene.
- 7. (Cancelled)
- 8. (Cancelled)
- 9. (Previously presented) The floor covering as claimed in Claim 8, wherein the grafting degree is 1% to 5%.
- 10. (Previously presented) The floor covering as claimed in Claim 1, wherein the proportion of grafted copolymer in relation to the total weight of the polymeric binder is 5% to 25% by weight.
- 11. (Previously presented) The floor covering as claimed in Claim 1, wherein the elastomer is cross-linked with at least one cross-linking agent based on an organic peroxide and optionally a co-cross-linking agent.
- 12. (Previously presented) The floor covering as claimed in Claim 11, wherein the co-cross-linking agent is an isocyanuric acid derivative or an acrylate or a methacrylate derivative derived from a polyol.

- 13. (Previously presented) The floor covering as claimed in Claim 1, which further comprises a filler, a pigment, a processing aid, an antioxidant, a static eliminator, a UV stabilizer or a slip agent.
- 14. (Previously presented) The floor covering as claimed in Claim 13, wherein the filler is a mixture of platelet-shaped and crystalline mineral intergrowths.
- 15. (Previously presented) The floor covering as claimed in Claim 1, having a variable color pattern and a homogeneous design.

16-24 (withdrawn)

25. (Currently amended) A The floor covering comprising as polymer binder at least one elastomer based on at least one polyolefin with a density < 0.910 g/cm³, and at least one grafted copolymer,

wherein the proportion of grafted copolymer in relation to the total weight of the polymeric binder is 5% to 25% by weight; and

wherein the grafted copolymer is maleic acid anhydride grafted HD polyethylene.